


SPECIFICATION \ CONNECTION		BIPOLAR					
AMPS/PHASE		0.24					
RESISTANCE/PHASE(Ohms)@25°C		20.40±10%					
MINIMAL THRUST(N)@300 PPS		10.00					
LEAD(mm)		4.00					
LINEAR TRAVEL/STEP(mm)		0.02					
STEP ANGLE(°)		1.80					
STEP ACCURACY(NON-ACCUM)		±5.00%					
LEAD TYPE		AWG 26					
TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)							
AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F]							
INSULATION RESISTANCE 20 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)							
INSULATION CLASS B 130°C[266°F]							
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE )							
AMBIENT HUMIDITY MAX.85%(NO CONDENSATION)							
<div>STEPPERONLINE®</div>			APVD	LDJ	12.18.2023	STEPPER MOTOR	
			CHKD				
		1.5:1	DRN	ZPJ	12.18.2023	8N11S0244DC3-150RS	
		SCALE	SIGNATURE		DATE		


TYPE OF CONNECTION (EXTERN)		MOTOR	
PIN NO	BIPOLAR	LEADS	WINDING
1	A —	RED	
2	A\ —	RED/WHT	
3	B —	GRN	
4	B\ —	GRN/WHT	

FULL STEP 2 PHASE-Ex. ,  
WHEN FACING MOUNTING END (X)

STEP	A	B	A\	B\		CCW
1	+		-			
2		-		+		
3	-		+			
4		+		-		

TYPE OF CONNECTION (EXTERN)		MOTOR	
PIN NO	BIPOLAR	LEADS	WINDING
1	A —	RED	
2	A\ —	RED/WHT	
3	B —	GRN	
4	B\ —	GRN/WHT	

FULL STEP 2 PHASE-Ex. ,  
WHEN FACING MOUNTING END (X)

STEP	A	B	A\	B\		
1	+		-			CCW
2		-		+		
3	-		+			
4		+		-		

